



Atom interferometry sensors

Fiodor Sorrentino

INFN - Sezione di Genova

Formerly at:

Dipartimento di Fisica & LENS, Università di Firenze & INFN






Outline




- Introduction to quantum sensors
 - atom optics and ultracold atoms
 - atom interferometers
- Precision measurements with quantum sensors
 - inertial sensing and geophysical applications
 - fundamental constants: G and recoil measurements
 - tests of fundamental physics (GR, quantum gravity)
 - other applications
- Future prospects
 - advanced atom interferometers
 - future space experiments




Ultracold atoms and atom optics



Lenses




Beam splitters



Atom interferometry sensors

Matter-wave interferometry

Quantum interference





Interference of transition amplitudes

$$P(|\psi_i\rangle \rightarrow |\psi_f\rangle) = |A_I + A_{II}|^2 = |A_I|^2 + |A_{II}|^2 + 2\text{Re}(A_I A_{II}^*)$$

de Broglie wave $\lambda_{\text{dB}} = h/mv$

- *with electrons since 1953*
- *with neutrons since 1974*
- *with atoms since 1991*

Atom interferometry



atomic flux at **exit** port 1
at **exit** port 2


- atom optics
- different internal states / isotopes
- phase difference may depend on:
 - accelerations
 - rotations
 - photon recoil
 - laser phase
 - laser frequency detuning
 - electric / magnetic fields
 - interactions with atoms / molecules



Possible applications of AI

- Already achieved:
 - inertial sensing (accelerations, gravity gradients, rotations)
 - measuring fundamental constants (α , G)
- Proposed:
 - tests of GR (equiv. principle, limits on PPN parameters, Lense-Thirring, etc.)
 - quantum gravity (e.g. testing Newton's $1/r^2$ law at short distance)
 - GW detection
 - Test of fundamental symmetries (e.g. atom neutrality)
 - realization of mass unit (Watt balance)

Accelerations



$$\Delta\Phi_{acc} = kT_{drift}^2 \cdot a$$

$$\frac{\Delta\phi_{mat}}{\Delta\phi_{ph}} \sim \left(\frac{c}{v_{at}}\right)^2 \approx 10^{11} \div 10^{17}$$

Rotations



$$\Delta\Phi_{rot} = 2\pi \frac{2m_{at}}{h} A \cdot \Omega$$




$$\frac{\Delta\phi_{mat}}{\Delta\phi_{ph}} \sim \frac{m_{at}\lambda c}{h} \approx 5 \cdot 10^{11}$$



Present limitations of AI

- shot-noise limit to sensitivity $\sim 1/\sqrt{\dot{N}}$
 - atomic flux $\sim 10^{18} \text{ s}^{-1}$ with H ($\sim 10^{11} \text{ s}^{-1}$ with alkali)
 - in a 1-kW laser the photon flux is $> 10^{22} \text{ s}^{-1}$
- much lower path difference than in optical interferometers
 - better beam splitters, optical cavities
- nevertheless AI inertial sensors are already competitive
 - long term stability (bias & scale factor) and accuracy
- future developments to improve sensitivity
 - large momentum beam splitters
 - high flux atomic sources
 - sub-shot noise detection (quantum degenerate gases, etc.)
 - large size AI, μ -gravity, ultracold atoms

Raman pulse atom interferometer



Light-pulse AI inertial sensors


TRANSVERSAL PULSES

- the interferometer encloses an area
- used to measure rotations (GYROSCOPES)

With an acceleration g ,
the phase difference

$$\Delta\phi = 2k_{\text{eff}} \cdot (\alpha - 2(\Omega \times v)) T^2$$

where k is the laser wavenumber and T the time interval between laser pulses




LONGITUDINAL PULSES

- no area enclosed
- used to measure accelerations (GRAVIMETERS)

With an acceleration g ,
the phase difference


$$\Delta\phi = k_{\text{eff}} g T^2$$

where k is the laser wavenumber and T the time interval between laser pulses





Raman interferometry in a ^{87}Rb atomic fountain: QPN limit




Phase difference between the paths:

$$\Delta\Phi = k_c[z(0)]2z(T)] + \Phi_e$$

$$k_e = k_1 - k_2$$


$$\text{with } z(t) = -gt^2/2 + v_0t + z_0 \text{ \& } \Phi_e = 0$$

$$\rightarrow \Delta\Phi = k_e g T^2$$



Final population:

$$N_a = N/2(1 + \cos[\Delta\Phi])$$



$$T = 150 \text{ ms} \rightarrow 2\pi = 10^{-6} \text{ g}$$




$$S/N=1000 \rightarrow \text{Sensitivity } 10^{-9} \text{ g/shot}$$

A. Peters et al., Nature **400**, 849 (1999)

Atom interferometry sensors





Atom gravimeters (Stanford, Berlin, Paris)



resolution: 8×10^{-9} g in 1 second (Stanford)
 averaging down to 8×10^{-10} g after 10 min (Berlin)
 accuracy: $\sim 10^{-9}$ g, limited by tidal models

A. Peters, K.Y. Chung and S. Chu, *Nature* **400**, 849 (1999)
 H. Müller et al., *Phys. Rev. Lett* **100**, 031101 (2008)
 M. Hauth et al., *Appl. Phys. B* **113**, 49 (2013)
 P. Gillot et al., *Metrologia* **51**, L15 (2014)

Atom interferometry sensors



sensitivity: $6 \times 10^{-10} \text{ rad} \cdot \text{s}^{-1} \sqrt{Hz}$
 scale factor stability $< 5 \text{ ppm}$
 bias stability $< 70 \mu\text{deg/h}$

T.L. Gustavson, A. Landragin and M.A. Kasevich, *Class. Quantum Grav.* **17**, 2385 (2000)
 D. S. Durfee, Y. K. Shaham, M.A. Kasevich, *Phys. Rev. Lett.* **97**, 240801 (2006)

F. Sorrentino 23/09/2014

Atom interferometry sensors




Raman gravity gradiometer



$$\Delta\Phi = k_e g T^2$$



Raman gravity gradiometer




$$T=5 \text{ ms}$$

$$\text{resol.} = 2.3 \times 10^{-5} \text{ g/shot}$$

$$\Delta\Phi = k_e g T^2$$




Raman gravity gradiometer



$T=5 \text{ ms}$

resol. = $2.3 \times 10^{-5} \text{ g/shot}$




$T=50 \text{ ms}$

resol. = $1.0 \times 10^{-6} \text{ g/shot}$

$$\Delta\Phi = k_e g T^2$$




Raman gravity gradiometer




$T=5$ ms

resol. = 2.3×10^{-5} g/shot



$T=50$ ms

resol. = 1.0×10^{-6} g/shot




$T=150$ ms

resol. = 3.2×10^{-8} g/shot

$$\Delta\Phi = k_e g T^2$$




Raman gravity gradiometer




$T=5$ ms

resol. = 2.3×10^{-5} g/shot




$T=50$ ms

resol. = 1.0×10^{-6} g/shot




$T=150$ ms

resol. = 3.2×10^{-8} g/shot





$$\Delta\Phi = k_e g T^2$$



G. T. Foster et al., Opt. Lett **27**, 951 (2002)

F. Sorrentino 23/09/2014

Atom interferometry sensors



Short-term sensitivity to differential acceleration: $3 \times 10^{-9} \text{ g @ 1 s}$ (=QPN for 4×10^5 atoms)
 Allan variance $\sim 0.2 \text{ mrad @ } 10000 \text{ s}$, corresponding to $5 \times 10^{-11} \text{ g}$


F. Sorrentino et al., Phys. Rev. A **89**, 023607 (2014)

Misura Accurata di G mediante Interferometria Atomica

- Rb fountain gradiometer
- + set of source masses




See talk by G. Rosi
on Wed. 24 (sez. II)



<http://www.fi.infn.it/sezione/esperimenti/MAGIA/home.html>



G measurements: current status




G. Rosi, F. Sorrentino, L. Cacciapuoti, M. Prevedelli and G. M. Tino, Nature **510**, 518 (2014)

F. Sorrentino 23/09/2014

Atom interferometry sensors



From proof of principle to G measure



$\hbar/m$ and fine-structure constant

fine-structure constant

$$\alpha = e^2/4\pi\epsilon_0\hbar c$$

Value **7.297 352 568 x 10⁻³**

Standard uncertainty **0.000 000 024 x 10⁻³**

Relative standard uncertainty **3.3 x 10⁻⁹**

Concise form **7.297 352 568(24) x 10⁻³**

$$\alpha^2 = \frac{2R_\infty}{c} \frac{m_p}{m_e} \frac{m_{Cs}}{m_p} \frac{h}{m_{Cs}}$$




FIGURE 2 Basic (Ramsey-Borde) atom interferometer with four $\pi/2$ laser pulses as beam splitter






FIGURE 3 SCIs used in this experiment. The last two $\pi/2$ pulses contain four frequencies in two pairs, to simultaneously address both conjugate interferometers

S.-W. Chiow et al., PRL **103**, 050402 (2009)
R. Bouchendira et al., PRL **106**, 080801 (2011)


Atom interferometry sensors

Freely falling vs trapped atoms

- Light-pulse (Raman or Bragg) atom interferometry
 - highest precision and highest accuracy so far demonstrated
 - atomic wave-function evolves in the absence of external fields
- AI in optical lattices
 - No free fall or free expansion
 - Small intrinsic size of the sensor
 - but... perturbation by laser field and by interatomic collisions






Short-range force measurements



- Characterization of the Casimir-Polder effect
- Exotic theories predict violations of Newton's law on some length scale
- Effect parametrized through Yukawa potential
- experiment set limits in parameters space ($\alpha - \lambda$)



$$V(r) = -G \frac{m_1 m_2}{r} [1 - \alpha e^{-(r/\lambda)}]$$

Bloch oscillations in optical lattice



$$q(t) = q_0 + Ft/\hbar \quad \longrightarrow \quad \nu_B = \frac{F\lambda}{2h} = \frac{mg\lambda}{2h}$$

Bloch oscillations of ^{88}Sr



Bloch frequency $574.568(3)$ Hz

8000 photon recoils in 7 s

$g_{\text{meas}} = 9.80012(5) \text{ m/s}^2$

G. Ferrari et al., PRL 97, 060402 (2006)

Decoherence time > 500 s


M. Tarallo et al., PRA 86, 033615 (2012)

- Direct acceleration sensitivity limited by the small splitting ($\sim 1 \mu\text{m}$)
- However, acceleration via BO already employed for LMT splitters in free-fall interferometers



H. Mueller et al., PRL 102, 240403 (2009)

Sample compression

- Vertical size in final MOT $\approx 12 \mu\text{m}$ rms
- We reduce it to $4 \mu\text{m}$ with an optical tweezer








Optical elevator



Atom-surface position jitter $< 1 \mu\text{m}$

F. Sorrentino et al., Phys. Rev. A **79**, 013409 (2009)

Resonant tunneling




V. V. Ivanov et al., PRL **100**, 043602 (2008)

$$\delta g/g \simeq 5 \times 10^{-7}$$

Atom interferometry sensors



Test of EP with bosons & fermions




measurement of the Eötvös ratio at the 10^{-7} level

M. Tarallo et al., PRL **113**, 023005-1 (2014)


Possible scheme for MAGIA Advanced

- Combining the advantages of the two methods
 - free fall: large splitting $\rightarrow$ large sensitivity
 - BO in optical lattice: small spatial scale & long coherent evolution
- Experimental sequence with
 - LMT splitter with N photon recoils and free fall for a time t
 - trapping in optical lattice and BO for time T
 - free fall for time t and recombination pulse with N photon recoils
 - already shown with Rb: R. Charrière et al., PRA 85, 013639 (2012).
- Two configurations with increasing sensitivity
 - MAGIA ADV 1:** $t=0.2$ s, $T=0$, $N=20$, sens. $\sim 3 \times 10^{-10}$ g/shot
 - MAGIA ADV 2:** $t=10$ ms, $T=10$ s, $N=20$, sens. $\sim 10^{-11}$ g/shot






Future of AI inertial sensors

- Compact and transportable system without performance degradation
 - ground applications (geophysics)
 - space applications (satellite geodesy, inertial navigation, tests of fundamental physics): $\Delta\phi = kgT^2$
- Novel schemes to improve sensitivity / accuracy
 - high-momentum beam splitters (up to 100 hk demonstrated)
 - coherent / squeezed atomic states to surpass QPN detection
 - large size AI (some 10 m towers already developed)
- New applications
 - GW, quantum gravity, etc.



LMT beam splitters

- H. Müller et al., PRL **102**, 240403 (2009)
- S.-W. Chiow et al., PRL **107**, 130403 (2011)
- G. D. McDonald et al., PRA **88**, 053620 (2013)




Atom interferometry sensors



Other possible applications of AI

- Fundamental physics
 - test of equivalence principle
 - measurement of gravitational red shift
 - test of atom neutrality
 - GW detection
 - quantum gravity
 - force measurements at micrometer scale
 - gravity for antimatter
- Metrology
 - definition of mass unit through Watt balance
- Earth observations
 - ground (mineral & oil explor., volcano monitoring, earthquake forecast)
 - airborne (underground structures, cavities, mineral & oil exploration)
 - satellite (geoid mapping, inertial navigation)

AI measurements in space



$$\Delta\phi = kgT^2$$

- Terrestrial AIs achieve differential gravity accuracy approaching $\sim 10^{-11}$ g with $T \sim 0.1$ s
- In space $\sim 10^{-15}$ g or better is foreseen with $T \gg 1$ s with same splitting
- Main issues to address for AI experiments in space:
 - TRL (lot of work in progress)
 - Motivation for space (on ground, large T requires long free-fall distance)
 - Understanding noise and error sources (test bench experiments on ground)




Space Atom Interferometers



ESA contract n. 20578/07/NL/VJ
AO-2004-064/082
Contract officer: Dr. L. Cacciapuoti

Project coordinator: Prof. G. M. Tino
Dipartimento di Fisica and LENS
Università di Firenze, Italy



F. Sorrentino et al., *A compact atom interferometer for future space missions*,
Microgravity Sci. Technol. **22**, 551 (2010)





try sensors



TRL of AI





SAI




QUANTUS
DLR

Scheme	State-of-the Art	iSense Goals	
		Technology Platform	Integrated Sensor
	 1m^3 , 100kg, 500W	 0.05m^3 , 10kg, 40W	 Demonstrator: Backpack-Size Gravity Sensor 0.1m^3 , 20kg, 50W Sensitivity: $1\mu\text{g}/\text{Hz}^{1/2}$ virtually drift-free
	 2m^3 , 200kg, 100W	 Integrated Optics 0.001m^3 , 2kg, 5W	
	 0.1m^3 , 50kg, 1kW	 Atom Chip 0.01m^3 , 5kg, 1W	





I.C.E.
Atom Interferometry in Microgravity

G. Tino et al., *Precision Gravity Tests with Atom Interferometry in Space*, Nuclear Physics B **243**, 203 (2013)




Atom interferometry sensors



O. Carraz et al., arXiv:1406.0765 (2014)

AI & GW detection

G. M. Tino, F. Vetrano and C. Lämmerzahl Eds., Special Issue on Gravitational waves detection with atom interferometry, Gen. Relativ. Gravit. **43**, 1901 (2011)






Conclusions

- New atomic quantum devices have been developed with unprecedented sensitivity using ultracold atoms and atom optics
- Applications: fundamental physics, Earth science, space research
- MAGIA: statistical & systematic errors at the 100 ppm level
 - QPN limited gravity gradient measurement down to several hours
 - more in G. Rosi's talk tomorrow
- Atom interferometry with ultracold ^{88}Sr
 - Fast and efficient cooling down to nK temperature
 - Long coherence time up to 500 s
 - Optical atomic clock and gravity sensor in the same device
- Future prospects: advanced atom interferometers for gravitational physics
 - gravity sensor with free fall + BO in optical lattice
 - large interaction time within small size
 - LMT splitters + high flux atomic source
 - foreseen G measurements down to the ppm level and WEP test @ 10^{-13}
 - demonstrators for GW detection
- Well developed laboratory prototypes, first transportable devices, work in progress for space-compatible systems
- Expected large improvements in next future



The team



Guglielmo M. Tino's group web page: <http://coldatoms.lens.unifi.it>